


SONY

Beamforming Microphone

MAS-A100



Hands-free ceiling beamforming microphone with speech reinforcement capability



The MAS-A100 is a state-of-the-art speech reinforcement* and recording solution. Attaching and positioning lavalier microphones is time-consuming, and handheld microphones restrict movement. However, the Beamforming Microphone is simply affixed to the ceiling, then ready to use – leaving the orator location-free, hassle-free and hands-free to focus on presenting. *Loud speaker system is required for speech reinforcement

Dedicated channels for speech reinforcement and recording

Our comprehensive solution employs audio volume stabilisation and clear audio processing to produce sharp recordings. The MAS-A100 has two channel outputs. The dual output channel enables speech reinforcement and recording simultaneously. The dedicated rec channel records with a wider capture range and optimal intelligibility – perfect for lecture capture.

Simple installation and management

Supporting Dante® and PoE, MAS-A100 links with third-party systems via a single cable connection. Auto-calibration streamlines system configuration, and settings can easily be adjusted via the network using free MASM-1 management software. With simple settings, central management and no need to monitor battery use, MAS-A100 is a convenient classroom audio solution.



Specifications

Networking	
Cable requirements	Cat5e UTP or higher
Audio	
Frequency response	100-10,000 Hz *
Sensitivity	0 dBFS/Pa at 1 kHz *
Maximum SPL	94 dB SPL
Signal to noise ratio	75 dB (A-weighted, 1 kHz, 1 Pa) *
Latency	Under 24 ms (Not including Dante latency)
Self noise	19 dB SPL (A-weighted) *
Dynamic range	75 dB *
Dante digital output	
Channel count	2 channels (Main, Rec) with Dante
Sampling rate	48 kHz
Bit depth	24
Audio interface	Dante, AES67
Digital Signal Processing	
Audio technologies	
	Beamforming
	Feedback reducer
	Automatic gain control
	Noise reduction
	Noise gate
	Automatic calibration with test signal
	Equalizer
	API for external control system
Performance	
Maximum noise reduction	24 dB
Maximum feedback reduction	32 dB
Configuration	
Mic gain (output volume)	-60 dB ~ +12 dB
Capture range	narrow/standard/wide
Feedback reduction	low/middle/high
Noise reduction	low/middle/high
Noise gate	off/low/middle/high
Equalizer	Fixed 5-band, ±12 dB (1 dB Step)
General	
Connector type	RJ45
Power requirements	Power over Ethernet (PoE), Class 0
Power consumption	13 W, maximum 9 W@25°C, typical
Weight	Approx. 1 kg (2 lb 3.2 oz) (main unit only) Approx. 1.3 kg (2 lb 14 oz) (with ceiling bracket)
Dimensions	Φ : approx. 240 mm (9 1/2 inch) Height : approx. 50 mm (2 inch)
Control browser (MAS-A100)	Google Chrome
Operating temperature range	0-40 °C
Operating humidity	20 % to 80 % (no condensation allowed)
Storage temperature	-20 °C to +60 °C (-4 °F to 140 °F)
Storage humidity	20 % to 80 % (no condensation allowed)
Supplied accessories	Ceiling bracket (1) Safety regulations (3) Template (1)

* Not Including signal processing

Distributed by

©2020 Sony Electronics Asia Pacific Pte Ltd. All rights reserved.
 Reproduction in whole or in part without written permission is prohibited.
 Features and specifications are subject to change without notice.
 The values for weight and dimension are approximate.
 Some images in this brochure are simulated.
 "SONY" is registered trademark of Sony Corporation.
 All other trademarks are the property of their respective owners.





www.pro.sony

MAS-A100 Beamforming Microphone A hands-free lecture and presentation solution

Introducing Sony's beamforming ceiling microphone with advanced speech reinforcement technology – enabling truly hands-free lectures and presentations.



The MAS-A100 Beamforming Microphone features a range of unique Sony's technologies which work together to create the ultimate hands-free lecture and presentation solution.



Beamforming and Intelligent Feedback Reducer

The integration of beamforming technology and our market-leading Intelligent Feedback Reducer produces clear audio with hands-free speech reinforcement, leaving the presenter hands-free. Sony's high-performance digital signal processing and unique algorithms extract speech sound while suppressing unwanted feedback (howling).

Noise reduction

Our Beamforming Microphone incorporates advanced noise reduction technologies to minimise ambient noise. Stationary background noise arising from projectors and air conditioning are automatically detected and reduced to achieve clear sound resulting in better intelligibility and, ultimately, better understanding for listeners.

Automatic gain control


The MAS-A100 has a useful inbuilt volume normalisation feature to maintain stable volume regardless of the distance between the presenter and the microphone, leaving the presenter free to move around the space without the audio quality deteriorating. Automatic gain control adjusts the strength of the signal received to ensure clear and consistent sound for easy listening.

Automatic calibration



The Beamforming Microphone optimises the parameters of audio processing for speech reinforcement automatically. The microphone generates a test signal, which is captured by the loud speakers. The system then calculates and configures the parameters for speech reinforcement. This calibration is required only on initial installation, minimising time-consuming set-up and system maintenance.

1. Generate test signal
2. Capture test signal from loud speakers
3. Calculate and configure optimal parameters for speech reinforcement

Connect to Dante audio system



Connect to Analog audio system



Microphone Array System Manager (free download)

Our comprehensive solution includes free Microphone Array System Manager software (MASM-1). The software supports installation and configuration of initial settings, as well as monitoring, operations and firmware management. MASM-1 is a total management solution, enabling users to manage multiple microphones in multiple locations centrally and easily via the local network.

Additional features

Dante and PoE compatibility

The MAS-A100 is compatible with third-party Dante mixers, converters and other devices, as well as power over ethernet (PoE). There's no complicated wiring – a single cable can connect the microphone to the system.

Status LED

The microphone has an inbuilt status LED, enabling both instructor and operator to easily recognise the microphone status.

API

Our Beamforming Microphone can be operated by API, permitting simple external control and customisation as well as linking with existing systems.